

# **Confidential Report**

Our Ref: 23/59955C3/07/22







Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 20 July 2022

Our Ref: 23/59955C3/07/22

Your Ref: ---

Page: 1 of 5

Client: Kobefab International B.V.

De Vest 62

5555 XP Valkenswaard

Netherlands

Job Title: Fire Test on One Fabric Sample

Clients Order Ref: ---

Date of Receipt: 12 July 2022

Date Test Started: 20 July 2022

Description of Sample: One sample of fabric, which was referenced by the client as;

Project Number: 2222. Kobe Name: Akila FR. Stated to be 100% Polyester.

Work Requested: We were asked to make the following fire test:

IMO FTP Code 2010:Part 8

- \* subcontracted test, UKAS accredited
- \*\* subcontracted test, EN ISO/IEC 17025 accredited
- \*\*\* not UKAS accredited



Note: This report relates only to the items tested.



Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk Website: www.bttg.co.uk

Date: 20 July 2022

Our Ref: 23/59955C3/07/22

Your Ref: ---

Page: 2 of 5

**Client:** 

#### Kobefab International B.V.

# **Product Description**

Company Name	Kobefab International BV	
FABRIC		
Type of Furniture, e.g., Seat, Sofa, Office Chair, etc;.	Upholstery for all furniture	
Name and/or Identification of the Product Tested	AKILA FR	
Materials of the Product and its Composite Ratio (i)	100% Polyester	
Composition of Weave (ii)	Knitted	
Density (Number/Inch) the Number of Threads per Inch in both warp and weft; and	Warped Fabric	
Yarn Number Count	Warp 1: 150 Denier Warp 1: 50 Denier	
Thickness (mm)		
Mass per Unit Area (g/m²)	506 g/m2	
Colour and Tone (iii)	Plain fabric	
Method and Quantity of Fire Retardant Treatment	Back coating 90 gr/m2	
FILLINGS		
Material (Name of Manufacturer, Type Designation)		
Type of Filling Material (eg. Foam, Polyester Fibre etc.)		
Weight per Unit Volume (kg/m³)		
Method and Quantity of Fire Retardant Treatment		

- (i) Such as wool, nylon, polyester, etc.
- (ii) Such as plain, weave, twilled.
- (iii) If the product has a pattern, the representative colour shall be described.





1066



Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 20 July 2022

Our Ref: 23/59955C3/07/22

Your Ref:

Page: 3 of 5

Kobefab International B.V. Client:

Testing to IMO FTP Code 2010: Part 8

**Test for Upholstered Furniture** 

## Conditioning

Immediately prior to testing the samples was placed in indoor ambient conditions for 72 hours and then conditioned in a standard atmosphere of 23±2°C temperature and 50±5% relative humidity for at least 16 hours.

The samples were tested in a room of volume 25m<sup>3</sup> and 25°C.

#### **Procedure**

The samples was tested in accordance with IMO FTP Code 2010: Part 8 using ignition sources 0 and 1. The sponsor sampled the material and the specimens were cut from the sample received to the dimensions set out in the standard.

The sample was tested over non-fire retardant polyurethane foam with a density of approximately 20-22kg/m<sup>3</sup>.

## Requirements

No progressive smouldering or flaming within 1 hour of the placement of the cigarette. Ignition Source 0

Ignition Source 1 All progressive smouldering and flaming to cease within 120 sec of removal of the burner tube.

# **Cigarette Specification (Source 0)**

Dimensions (mm) 69mm x 8.0mm

Mass (g) 0.85 Smouldering Rate (mins/secs) 10m 06s







Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

20 July 2022 Date:

Our Ref: 23/59955C3/07/22 Your Ref:

> Page: 4 of 5

**Client:** Kobefab International B.V.

## **Results**

### Cigarette Test - Source 0

Specimen No.	1	2
Extinction Time (smouldering) (min)	28	DNP
Time of cover split	DNO	DNO
Melting (Yes/No)	Yes	Yes
Dripping (Yes/No)	No	No
Charring (Yes/No)	Yes	Yes
Progressive Smouldering (Yes/No)	No	No
Observations	DNO	DNO
Pass/Fail	PASS	PASS

#### **Result of the Cigarette Test: Pass**

### Propane Flame Test – Source 1

Specimen No.	1	2
Time of Ignition (s)	5	5
Extinction time of flames after removal of burner (s)	1	1
Time to Cover Split (s)	7	6
Melting (Yes/No)	Yes	Yes
Dripping (Yes/No)	No	No
Charring (Yes/No)	Yes	Yes
Progressive smouldering (Yes/No)	No	No
Observations:		
Pass/Fail	PASS	PASS

Result of the Flame Test: Pass

Acronym

DNP - Did not propagate ES – Escalating smouldering BTE - Burnt to extremities



1066

EC – Escalating combustion DNS - Material did not split ME - Manually extinguished DNO – Did not observe time of event



Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

20 July 2022 Date:

Our Ref: 23/59955C3/07/22 Your Ref:

Page: 5 of 5

Kobefab International B.V. Client:

#### Comment

In our opinion, based on the test carried out on the sample supplied; the results indicate that the sample meets the requirements according to IMO FTP Code 2010:Part 8.

Where required to make a judgement to any pass/fail criteria an estimation of uncertainty of measurement has been taken into account. Under our Policy we have used a non-binary decision rule.

See our decision rules Policy (http://www.bttg.co.uk/decision-rules-policy) for further information.

# **Uncertainty Budget**

Measurements: ±2mm Timings: ±2 seconds.

...... B Bland, Technical Customer Services Officer

Countersigned by:..... ..... P Doherty, Manager

Enquiries concerning this report should be addressed to Customer Services.





1066